STRUB Lead substitle 9598

Additive for unleaded gasoline

Art.-No. 30548

Description
Additive for unleaded gasoline. With this additive, unleaded gasoline becomes a full replacement for leaded gasoline. Necessary for all 2-stroke and 4-stroke gasoline engines that would have to run on a leaded fuel due to soft valve seats in the engine design. By adding BLEIERSATZ 9598, unleaded gasoline can be refueled without any problems. The addition is made before refueling and can also be used for older injection engines with and without turbo.

Note
This additive has been used successfully since 1990 in Austria, 92 Sweden, 92 Norway, 93 Finland, 94 Denmark and 96 the Netherlands.
Leaded gasoline is no longer available in these countries.

Application
1 ml to 1 liter of unleaded gasoline or
1 liter to 1000 liters of unleaded gasoline

Features and advantages
- protects the valve seat
- keeps the valve seat clean
- prevents valve deformation and wear
- prevents deposits
- reduces wear
- increases engine life
- mixes with gasoline by itself
- does not contain heavy metals

Technical data

Color		light yellow
Density at 20°C	g/cm^3	0.825
Flash point	°C	71

Transport
ADR/SDR No dangerous goods

Disposal
LVA VeVA / EAK 14 06 03

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG
Swiss Tribology
Mühlemattstrasse 5
CH-6260 Reiden
phone +41 62 785 22 22
fax +41 62 785 22 33
strub@strub-lube.ch
www.strub-lube.ch