



STRUB Vulcair Synt 761

Special oils for the lubrication of all types of pneumatic tools

Art.-No. 31512



Description

Low-viscosity, fully synthetic, rapidly biodegradable hammer drill oil. At up to 3000 strokes per minute, highly effective lubrication and cooling of all moving parts is a prerequisite for trouble-free operation. The formulation of STRUB Vulcair Synt 761 has been adapted to the latest findings.

Application

STRUB Vulcair Synt 761 is used for the lubrication of pneumatically operated hammer and drill systems, especially at low outside temperatures.

Features and advantages

- very good lubricity
- very good high pressure properties
- very favorable cold behavior
- good corrosion protection

Technical data

Color		blue
Density at 20°C	g/cm ³	0.942
Viscosity at 40°C	mm ² /s	20.7
Viscosity at 100°C	mm ² /s	5.2
Viscosity index VI		200
Flash point	°C	220
Pour point	°C	< - 40

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 06

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.