

# STRUB Vulcair

Special oils for the lubrication of all types of pneumatic tools



## Description

High-quality special oils for the lubrication of all types of pneumatic tools. STRUB Vulcair form a distinctive, wear-reducing, well-adhering lubricating film. They bind moisture (water) and carry it out of the system, thus largely preventing icing. STRUB Vulcair are based on selected high-quality mineral oil raffinates.

## Application

STRUB Vulcair meet the requirements of renowned manufacturers of pneumatic tools such as Atlas-Copco, Ingersoll-Rand and others. Observe application viscosity according to regulations.

## Features and advantages

- very good high pressure properties
- very good corrosion properties
- good cleaning effect

## Technical data

ISO		32	46	68	100	220
Art. No.		30917	31243	32040	32041	32042
Color		brown	brown	brown	brown	brown
Density at 20°C	g/cm <sup>3</sup>	0.860	0.875	0.876	0.878	0.883
Base oil viscosity at 40°C	mm <sup>2</sup> /s	32	46	68	100	220
Application viscosity at 40°C	mm <sup>2</sup> /s	24	35	52	80	172
Flash point	°C	130	130	132	134	135
Pour point	°C	- 30	- 30	- 30	- 30	- 21

## Transport

ADR/SDR No dangerous goods

## Disposal

LVA VeVA / EAK: 13 02 06

## Information

Other viscosities available on request. For use when working near water, the biodegradable, fully synthetic hammer drill oils STRUB VULCAIR SYNT 825 or 540 XL are available.

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.