



STRUB Vulcan Futura CF 2900, 2915, 2922, 2932

Heavy Duty
High-performance cutting oils

Description

STRUB Vulcan Futura CF 2900, 2915, 2922, 2932 are chlorine and heavy metal free high performance cutting oils with the latest QPLC technology. The focus is on quality, performance, durability and cost/benefit.

Application

STRUB Vulcan Futura CF 2900 cutting oils are successfully used for any operations but also threading, broaching, reaming of difficult-to-machine alloys such as chrome steel, "surgical steels" (implants), titanium, free-cutting steels, magnetic core irons, aluminum. It is also suitable for non-ferrous metals (copper corrosion test ASTM, D 130 / IP 154 1b).

Features and advantages

- free of chlorine and heavy metals
- low in aromatics
- synthetic synergistic additives
- oxidation stable
- low evaporation loss
- increased tool life
- high economic efficiency
- excellent surface finish
- low mist
- strong lubricating film
- skin-friendly

Technical data

STRUB Vulcan Futura Art.-No.		CF 2900 30573	CF 2915 31019	CF 2922 30822	CF 2932 31723
Appearance	ISO 2049	brown, clear	brown, clear	brown, clear	brown, clear
Density @ 20 °C	g/cm ³	0.858	0.864	0.865	0.864
Viscosity @ 40°C ASTM D 445	mm ² /s	10	15	22	32
Flash Point	°C	>135	160	>200	>200
Copper Corrosion ASTM D 130	3h (100°C)	1b	1b	1b	1b

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 07

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.