

1 von 1

STRUB Antifoam 54

For all water-miscible cooling lubricants

Art.-No. 32691

Description

STRUB Antifoam No. 54 is a whitish, highly viscous defoamer which is easy to incorporate, for all water-miscible cooling lubricants.

Application

STRUB Antifoam No. 54 is used temporarily for foam peaks (shaving foam e.g. caused by the introduction of surfactants, air etc.). The product shows no undesirable properties in surface treatment.

Dosage

Depending on the foam quantity, usually 0.005% to a maximum of 0.01% is added to the emulsion quantity. STRUB Antifom No. 54 is easily dispersible in the emulsion, even easier pre-diluted with water. The defoamer should nevertheless be added at points of high fluctuation (e. g- emulsion return or suction pump).

Technical data

Appearance	visual	white
Density at 20°C	g/ml	1.02
pH value	Pur	7.4

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 16 03 06

ISO 9001|14001, Version 1: 26.10.2016 / DF

Note

Store frost-free. Shake or stir after prolonged storage.

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch