

STRUB Gas Engine Oil 43 MA

Gas engine oil for operation with landfill, sewage or Biogas and for gas engines operating with special gases

Art. No. 30327

Description

STRUB Gas Engine Oil 43 MA is a special oil for use in gas engines. Specially selected base oils and a newly developed additive package guarantee excellent oxidative and thermal stability.

Application

STRUB Gas Engine Oil 43 MA is primarily suitable for operation with landfill gas, sewage gas or biogas, as well as for gas engines in operation with special gases, where increased pollution is to be expected. Please observe the manufacturer's instructions!

Optimum oil change intervals, according to the recommendations of the gas engine manufacturers. Accompaniment and advice by laboratory analyses necessary.

Features and advantages

- good operational reliability and oil life
- very high alkalinity reserve
- reliable wear and corrosion protection
- reduced deposits in the combustion chamber

Specifications

MIL-L-2104B/ 2104C, Jenbacher engines BR 1, 2, 3, 4 according to technical instruction TA 1000-1107, TMW, Iveco, MAN M 3271-2; MTU

Approvals:

Tedom Engines for biogas

Technical data

SAE		40
Density at 20°C	g/cm ³	0.886
Viscosity 100°C	mm ² /s	13.4
40°C	mm ² /s	122
Flash point COC	°C	250
Pour point	°C	- 18
TBN	mgKOH/g	9.7
Sulfated ash	%	0.94

Transport

ADR/SDR: No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.