

STRUB HC 1540

Semi-synthetic quality gas engine oil for stationary engines

Art. No. 30205



Description

STRUB HC 1540 is a quality gas engine oil based on mineral and HC oil raffinates with high alkalinity reserve. Specially selected, low-evaporation base oils and a newly developed additive package guarantee high oxidative and thermal stability.

Application

Preferred for use in all gas engines, including supercharged ones, for sewage and biogas operation, also for operation with natural gas, when extended oil change intervals are required. STRUB HC 1540 is primarily suitable for stationary diesel engines, emergency power plants, CHP units, etc.

Features and advantages

- long oil life
- safe wear and corrosion protection
- strong cleaning due to balanced HD and EP active ingredients
- reduced deposits in combustion chamber and exhaust catalyst

Specifications

Caterpillar
Erdgas, Biogas
Deutz, MAN, MTU

Technical data

SAE		10W/40
Density at 20°C	g/cm ³	0,859
Viscosity 100°C	mm ² /s	13.7
	40°C	90
Viscosity index		160
Flash point COC	°C	240
Pour point	°C	< -40
TBN	mgKOH/g	9.5
Sulfated ash	%	0.96

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.