

Flex pump aqueous AD gray

self-priming hybrid pump for AdBlue®, suitable for 200 lt

Art.-No. 954071

Description

The flex pump aqueous AD gray is a self-priming hybrid pump for AdBlue®, antifreeze, water, suitable for 200 It plastic drums with 2" drum screw connection. Refueling system for trucks, buses, construction machinery, agricultural vehicles. Low-wear hybrid pump: rotor blades lay against the inner wall of the pump chamber during priming operation.

Technical Data

- Viscosity: low •
- Pump type: hybrid pump self-priming •
- Material pump housing: plastic
- Voltage: 230 V/50 Hz •
- power consumption: 2,6 A •
- Power: 550 W •
- Low-wear hybrid pump principle •
- Suitable for continuous operation •
- Delivery rate: 48 l/min
- Connection suction outlet: 3/4" IT •
- Barrel thread: DN 50 (2") M 64 x 4 .
- Dispensing valve: DN 20 (3/4") hose nozzle, outlet ø 19 mm, with dispensing gun holder and drip cup •
- Automatic nozzle A 2003-KS, plastic (without locking catch) •
- dispensing hose: 8 m •
- Suction tube: 1000 mm •
- Cable length: 4m
- Medium temperature max.: -5°C to +30°C •
- Ambient temperature: -5°C to +40°C •
- Dimensions (W x D x H): 206 x 116 x 1250 mm •
- Protection class: IP 54
- Weight: 3,7 kg



The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

STRUB + Co. AG Swiss Tribology

Mühlemattstrasse 5 CH-6260 Reiden

phone +41 62 785 22 22 +41 62 785 22 33 strub@strub-lube.ch www.strub-lube.ch

ISO 9001|14001, Version 1: 12.12.2022 / DTA