

VITO 90

Filter system

Art.-No. 952027

Description

The VITO 90 can simply be placed in the processing plant for quick cleaning:

In no time at all, it can be used to maintain and clean all your containers - the patented, mechanical microfiltration of the VITO requires only a few minutes for this. The result is clean, high-quality cooling lubricants, oils and aqueous solutions - freed from chips and solids.

Advantages

- less wear
- less personnel costs
- less transport costs
- less storage costs
- fast amortization

Constant quality

- of your KSS
- of your workpieces

Easy handling

- automatic filtration
- fast pressure filtration
- low cleaning effort



Technical Data

Filtration capacity	up to 90 l./min
Filtration	Up to 5 ųm
Particle pickup	2,5
Cycle time	10 min (customizable)
Suction depth	~ 35 cm
Weight	9,2 kg
Temperature	max. 200°C
Material	Stainless steel 1.4301
Maximum power	500 Watt

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch

ISO 9001|14001, Version 1: 23.01.2023 / DTA 1 / 1