

STRUB Gearbox fluid grease 1740 EP 00

Fluid grease with EP additives

Art.-No. 30663

Description

High-quality fluid grease with pronounced high-pressure properties (contains EP additives), thus high lubricity. Good flexing stability and thus only very slight change in consistency. Good corrosion protection and high oxidation stability (aging resistance). Miscible and compatible with all other branded greases of the comparable type.

Application

Lubrication of grease-lubricated gears, wherever a fluid grease of NLGI class 00 is prescribed. For gear motors (such as BAUER gear motors) and with correspondingly good sealing for roller, ball and needle bearings. Very suitable for central lubrication systems Vogel, Delimont, Bielomatik etc. Temperature application range: - 25 to 100°C.

Technical data

Color	visual	brown
Base oil Viscosity at 40°C	mm ² /s	150
Drop point	°C	> 150
Fulling penetration (60 strokes)	10/mm / 25°C	415
NLGI class	DIN/ISO 2137	00
Stiffener		Lithium
Emcor corrosion test	Grading	0
Temperature application range	°C	- 25 to 100

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 12

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.