

1 von 1

STRUB Multi Duty Grease EP 1, 2 + 3

Greases without drop point

Description

STRUB Multi Duty Grease EP are infusible greases (without drop point). Careful manufacturing and the addition of high-quality additives result in greases with universal character.

Application

Due to the high temperature application range, it can still be used as a universal grease where lithium soap greases fail the service. Fields of application: Construction, garages, cement industry, mills, foundries, chemical industry, textile and machinery industry, transport industry, agriculture, etc.

Features and advantages

- wide temperature application range
- very good (EP) high pressure properties
- excellent adhesion, sealing and rust protection properties
- good water resistance, temperature stability, shear stability and extensive chemical resistance are further advantages of this grease

Technical data

STRUB Multi Duty Grease		EP 1	EP 2	EP 3
Art. No.		32033	30666	30677
Color		brown	brown	brown
Saponification type		Bentonit	Bentonit	Bentonit
Fulling penetration 25°C / 60H	1/10 mm	310 - 340	265 - 295	220 - 250
Kinematic viscosity of base oil at 40°C	mm²/s	480	480	480
Drop point		Infusible	Infusible	Infusible
Application range	°C	- 30°C to + 180	- 25°C to + 200	- 25°C to + 200
Short-term permissible peak temperature	°C	+ 200	+ 250	+ 250

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 12

ISO 9001|14001, Version 1: 28.07.2014 / MF

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch