

1/1

## **Vaseline Technical**

Technical petrolatum

Art.-No. 31816

## Description

Light yellow, easily spreadable, almost odorless fat.

## **Application**

Vaseline Technical is used for lubrication of various parts.

## **Technical data**

	Norm	Unit	Values
Color			white to slightly yellowish
Melting point	ASTM D 127	°C	38 - 80
Specific gravity at 100°C		g/cm <sup>3</sup>	0,79 - 0.85
Viscosity be 100°C		mm²/s	5 - 30
Penetration	Cast	1/10 mm	165 - 185

**Transport** 

ADR/SDR No dangerous goods

**Disposal** 

LVA VeVA / EAK: 12 01 12

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch

ISO 9001|14001, Version 1: 12.11.2021 / RSC