

# STRUB Vulcodur 100/150

Tempering oil

Art.-No. 31060

---

## Description

STRUB Vulcodur 100/150 is a semi-synthetic, low evaporation tempering oil. This product has been specially adapted to our synthetic bright tempering oils. The additive system guarantees highest thermal stability as well as oxidation resistance even under unfavorable operating conditions.

## Application

STRUB Vulcodur 100/150 is primarily used for tempering and stress relieving of hardened steel parts. The maximum operating temperature is 220°C.

## Technical data

Color, appearance		brown, clear
Density / 20°C	g/cm <sup>3</sup>	0.920
Viscosity 40°C	mm <sup>2</sup> /s	105
Viscosity 50°C	mm <sup>2</sup> /s	67
Viscosity at 200°C	mm <sup>2</sup> /s	2.9
Flash point COC	°C	280
Flash point COC	°C	320
Application temperature	°C	max. 220

## Transport

ADR/SDR No dangerous goods  
UN-Code inapplicable

## Disposal

LVA VeVA / EAK: 12 01 07

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.