

STRUB Vulcolube EP VI 300

Multigrade hydraulic oil

Description

STRUB Vulcolube EP VI 300 is a mineral oil-based multigrade hydraulic oil.

Application

STRUB Vulcolube EP VI 300 is particularly suitable for hydraulic systems which require a lubricant with very low viscosity-temperature dependence. This applies, among other things, to systems which are exposed to strongly changing or low outside temperatures.

Features and advantages

- outstanding viscosity-temperature behavior thanks to the high viscosity index
- very good wear protection
- excellent aging resistance
- compatible with all mineral oil compatible seals

Specifications

DIN 51524 - 3 (HVLP)

Technical data

ISO Art.-No.			15 30342	22 31150	32 30343	46 30982
Farbe	ISO 2049	-	red	red	red	red
Dichte bei 20°C	DIN 51757-1	g/cm ³	0.840	0.854	0.855	0.862
kin. Viskosität bei 0°C	ISO 3104	mm ² /s	58	83	150	225
kin. Viskosität bei 40°C	ISO 3104	mm ² /s	15	22	32	46
kin. Viskosität bei 100°C	ISO 3104	mm ² /s	5	6.6	8.6	11.4
Viskositätsindex	ISO 2909	-	291	290	258	251
Flammpunkt	ISO 2592	°C	139	169	161	190
Pourpoint	ASTM D 97	°C	-36	-33	-33	-33

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 01 13

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.