



1/1

## **STRUB Syntlube Transparent 38.3**

Universal lubricant, transparent

Art.-No. 33734

## Description

STRUB Syntlube Transparent 38.3 is a biodegradable synthetic lubricant that forms a transparent protective film and is effective in a temperature range from - 45°C to 160°C. The product is an amine-free, ecotoxicologically safe lubricant. It contains no additives of silicone or molybdenum disulfide. STRUB Syntlube Transparent 38.3 has excellent capillary action, penetrates into the pores of the metal surface and forms a non-measurable release film. It contains effective anti-corrosion, anti-wear and high pressure (EP) additives and is stable at high temperatures.

- Biodegradable according to European standard CEC-L-33-T-82 > 65 %.
- pronounced corrosion protection, infiltrates water
- high lubricity, as well as wear protection and EP properties
- can, if desired, be removed without residues using STRUB Monafix-T-Special aqueous alkaline cleaner (dilution 1 : 10 to 1 : 30), tri-perchloraethane.

## **Application**

STRUB Syntlube Transparent 38.3 is suitable for lubrication of all moving parts, joints, bolts, chains, etc. under high vibration and shock loads; wherever a transparent, well adhering film is desired.

## **Technical data**

i cerimicai aata	
Appearance	clear, yellow-brown liquid
Spec. wt. at 20°C	0.948 g/ml
Viscosity at 20°C	93.5 mm <sup>2</sup> /s
at 40°C	38.3 mm <sup>2</sup> /s
at 100°C	7.1 mm <sup>2</sup> /s
VI	150
Flash point COC	230°C

**Transportation** 

ADR/SDR No dangerous goods

Disposal

FVO VeVA / EAK 13 02 07

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch