



STRUB Syntlube Transparent 52.9

Fully synthetic industrial multipurpose oil

Art.-No. 33735

Description

STRUB Syntlube Transparent 52.9 is a biodegradable, fully synthetic lubricating oil which forms a transparent protective film. It can be used at temperatures from - 45°C to + 230°C. It does not contain organic greases, petroleum derivatives, silicones, molybdenum disulfides, graphites or Teflon (PTFE).

STRUB Syntlube Transparent 52.9 has excellent creep properties and forms a non-measurable protective film on the surface of the metal. Because it has a very low coefficient of friction of 0.03, its behavior as an antifriction agent is outstanding.

Application

STRUB Syntlube Transparent 52.9 is suitable for the lubrication of all moving parts such as joints, bolts, chains, tools, etc., which are subject to high vibration and shock loads and where a clean, transparent lubricating film is required.

Features and advantages

- biodegradable according to EU standard CEC-L-33-A-93 > 65 % •
- dissolves rust, removes sticky impurities from metal parts and cleans the surfaces
- prevents the formation of flash rust
- is extremely capillary and penetrates micropores and crevices •
- is a dry-holding liquid (water repellent) and forms a protective film against moisture •
- antistatic, therefore it repels dust and dirt.

Technical data

Color		dark brown, clear	
Density at 20°C	g/ml	0.9366	
Viscosity at 40°C	mm ² /s	52.96	
Viscosity at 100°C	mm ² /s	8.761	
Viscosity index		143	

Transportation ADR/SDR

No dangerous goods

Disposal

LVA VeVA / EAK

12 01 06

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

STRU	B +	Co.	AG
Swiss	Tril	bolo	gy

strub@strub-lube.ch www.strub-lube.ch