

STRUB Vulcochaine

Synthetic chain lubricants



Description

STRUB Vulcochaine are synthetic chain lubricants.

Application

A range of fully synthetic and temperature resistant chain oils for industrial use. Upper temperature limit at 260°C. Thermal decomposition occurs above 300°C.

Features and advantages

- very good lubricating effect
- distinct wear reducing properties
- good wetting capacity
- good oxidation resistance

Technical data

STRUB Vulcochaine	1000	1500	2200	3200	4500	5600	7500
Art. No.	31253	31254	31641	31255	32247	32498	31257
Color	light yellow	light yellow	light yellow	light yellow	light yellow	light yellow	light yellow
Density at 20°C	0.950	0.940	0.950	0.956	0.960	0.965	0.966
Viscosity 40°C mm ² /s	108	150	220	340	450	560	740
Viscosity 100°C mm ² /s	11.7	18.8	25	34	41	52	63
Flash point °C	270	250	250	250	250	250	250
Pour point °C	- 30	- 27	- 28	- 30	- 27	- 25	- 24

Note

STRUB Vulcochaine oils are compatible with mineral oil. Chains previously lubricated with mineral oil do not necessarily have to be cleaned before conversion. Compatibility with other synthetic chain oils must be checked on a case-by-case basis.

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 06

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.