

STRUB Syntolube HOT 60 (Chain 68)

Fully synthetic chain lubricant with high temperature resistance

Art. No. 31429



Description

Fully synthetic chain oil with very good lubricating effect, pronounced wear-reducing properties, good wetting capacity and excellent oxidation resistance.

Application

Oil-lubricated, thermally highly loaded chains in drying plants, etc.

Features and advantages

- Low evaporation tendency
- No resinification
- Free from environmentally harmful heavy metals
- Temperature resistance up to 220°C

Technical data

Features	Specifications	Unit	HOT 60 (Chain 68)
Color	visual		yellowish
Density at 20°C	DIN 51757	g/ml	0.914
Viscosity 40°C	ASTM D445, IP71	mm2/s	68
Viscosity 100°C	ASTM D445, IP71	mm2/s	10.7
Flash point	DIN ISO 2592	°C	260
Pour point	DIN ISO 3016	°C	- 38

Note

The above information is based on our current knowledge and experience. We reserve the right to make changes.

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 06

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Swiss Tribology Mühlemattstrasse 5 CH-6260 Reiden phone +41 62 785 22 22 fax +41 62 785 22 33 strub@strub-lube.ch www.strub-lube.ch