

# STRUB FC 531

Solvent-based rust protection, corrosion protection oil, 80 % VOC

Art.-No. 30579

---

## Description

STRUB FC 531 has been specially designed for spare parts storage, temporary storage and for transport preservation.

This rust preventive oil forms a light oily film on the material to be treated, and forms an excellent water displacing corrosion protection.

The film is oily, does not gum up and has a slight lubricating effect. It can be easily removed with petroleum, gasoline or alkaline industrial cleaners (e.g. with MONAFIX ECOCLEAN 3000).

The protective film is slightly brownish.

## Application

By spraying, dipping or with a brush. To prevent excessive evaporation of the solvent, these baths should be equipped with a lid.

To ensure that the water runs off everywhere with certainty, we recommend rotating or swiveling complicated workpieces. An immersion time of between 30 and 60 seconds should be observed.

## Technical data

Density	g/ml	0.810
Flash point g.T.	°C	62
Film thickness	µm	> 1.0
Drying time	min.	ca. 60
Protection time for indoor storage	Months	24
Protection time for outdoor storage	Months	6
Alkaline cleaning		good (VW 52.02)

## Transport

ADR/SDR No dangerous goods

## Disposal

LVA VeVA / EAK 14 06 03

## Levies

VOC-required to 80%

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.