

STRUB Vulcomet Protection 8000 BF-BM

Mineral oil-based dilutable corrosion protection concentrate

Art.-No. 31827

Description

STRUB Vulcomet Protection 8000 BF-BM is a mineral oil based highly effective corrosion protection concentrate, which is characterized by high compatibility with white spirits, low viscosity oils and other solvents (also halogenated hydrocarbons). STRUB Vulcomet Protection 8000 BF-BM is soluble in all common non-water miscible metalworking fluids, engine or gear oils. The concentrate is particularly suitable for post-greasing in solvent cleaning systems.

Application

STRUB Vulcomet Protection 8000 BF-BM is used where high corrosion protection is required.

Depending on the concentration used, an oily, non-resinifying protective film of varying protection duration remains after evaporation of the solvent. STRUB Vulcomet Protection 8000 BF-BM can be applied by all common methods if suitably diluted. Increased corrosion protection requirements for oils can usually be massively improved with a 2 to 5% application.

Features and advantages

- excellent corrosion protection for ferrous and non-ferrous metals with a very thin film
- water displacing effect •
- good lubricating properties .
- high economic efficiency due to high yield
- barium-free, removable with solvents and aqueous industrial cleaners

Technical data

| Color | | brown |
|------------------------------|----------------|--------|
| Density at 20°C | g/ml | 0.8865 |
| Viscosity at 20°C | mm²/s | 80 |
| at 40°C | mm²/s | 28 |
| Flash point | °C | > 150 |
| Pour point | °C | - 9 |
| Corrosion behavior (St1405): | | |
| Condensation water change | Cycles | 20 |
| climate | h | 24 |
| Salt spray chamber | | |
| Protection time at: | | |
| - Indoor storage | Months approx. | 12 |
| - shed storage | Months approx. | 3 |

Transport

ADR/SDR

kein Gefahrengut

Disposal

LVA VeVA / EAK 13 02 06

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

STRUB + Co. AG Swiss Tribology

Mühlemattstrasse 5 CH-6260 Reiden

phone +41 62 785 22 22 +41 62 785 22 33 strub@strub-lube.ch www.strub-lube.ch