

STRUB Vulcomet Protection 8035

Cleaner, rust inhibitor and dewatering fluid, VOC 70%.

Art.-No. 30607

Description

STRUB Vulcomet Protection 8035 can be used as cleaner and corrosion protection. The product is characterized by its excellent water separation properties.

STRUB Vulcomet Protection 8035 removes oils, greases, tar, bitumen and dust as well as all common contaminants on machines and workpieces. Cleaned surfaces and parts are subsequently protected against corrosion and can be stored temporarily at room temperature for further processing.

Application

The application possibilities are almost unlimited, all metals can be cleaned with STRUB Vulcomet Protection 8033. The main use of the product is in metalworking stores, car garages, locksmith's shops, electrical workshops of all kinds, etc. Everywhere where quick and thorough cleaning is required. It is used undiluted as supplied. Before further processing, the anti-corrosion oil must be washed down.

Features and advantages

- extremely good wetting capacity
- · Due to the formulation very skin-friendly, environmentally friendly, with very low toxicity
- well compatible with most materials and surfaces
- low aromatic content and pleasant odor
- · very long lifetime

Technical data

i Cerificai data		
Density at 20°C	g/cm ³	ca. 0.825
Flash point	°C	46
Initial boiling point	°C	170
Boiling point	°C	> 250
Viscosity at 40°C	mm²/s	5.0
Protection time at:		
- Indoor storage	Months	6 - 8
- External storage	Months	1 - 3

Transport

ADR/SDR N 1993 Flammable Liquid, N.O.S. (C10-C12 Isoparaffins), Class 3, VP III.

Disposal

LVA VeVA / EAK 14 06 03

Levies

VOC subject to 70 %.

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Swiss Tribology Mühlemattstrasse 5 CH-6260 Reiden phone +41 62 785 22 22 fax +41 62 785 22 33 strub@strub-lube.ch