

STRUB Vulcomet Protection 8045 BF-DW

solvent-based corrosion protection and dewatering fluid, VOC 71%.

Art.-No. 30609

Description

Corrosion inhibitor with water displacing properties and highest effectiveness for medium and long-term indoor and outdoor storage.

STRUB Vulcomet Protection 8045 BF-DW forms a soft wax-like, slightly greasy, non-sticky film which is elastic and insensitive to mechanical damage.

The protective film can be easily removed with all commercially available cleaners.

Application

Preservation of metals. Suitable also for galvanized surfaces (white rust), protection against acid vapors. Due to the wide range of application STRUB Vulcomet Protection 8045 BF-DW can be used everywhere. By spraying, dipping or with brush.

STRUB Vulcomet Protection 8045 BF-DW is ready to use and does not need to be diluted. The rust protection oil dries quickly.

Features and advantages

- universally applicable
- Water displacing properties increase the range of application

Technical data

Density at 20°C	kg/m ³	0.830
Flash point g. T. (AP)	°C	53
Film thickness	µm	3
Yield	m ² /l	15
Drying time at RT	Min.	ca. 60 - 80
Protection time at:		
- Indoor storage	Months approx.	12 - 14
- outdoor storage	Months approx.	6

Transport

ADR/SDR Class 3, packing group III

Disposal

LVA VeVA / EAK 14 06 03

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.