

# STRUB Vulcomet Protection 9000-7 DW

Solvent-based corrosion protection and dewatering fluid, 78%.

Art.-No. 31576

## Description

STRUB Vulcomet Protection 9000-7 DW is a low viscosity corrosion protection oil for the protection of machines, precision mechanical products and small parts made of steel. The product is particularly suitable for the preservation of high-precision tools, e.g. tool holders, collets during production and as transport protection. The product leaves an oily protective film.

## **Application**

Normally, the application of corrosion protection products that have a water displacing effect is carried out in immersion baths. In addition, STRUB Protection 9000-7 DW can also be sprayed very well. The drying time can be significantly reduced by exposing the treated parts to 60-80°C in a heating cabinet/circulating air. After evaporation of the solvent, a very thin, vaseline-like hand sweat neutralizing protective film remains on the metal, which does not resinify. The protective film can be removed with petroleum, benzine, circulation cleaner, tri, per-chloraethane or alkaline cleaners, such as STRUB Monafix Ecoclean 3000 or STRUB Monafix-T-Special in aqueous dilution.

### Features and advantages

- economical application
- long bath life
- suppresses corrosion attack by fingerprints or hand perspiration
- high resistance to the introduction of acidic and alkaline media

### **Technical data**

Appearance		brown liquid
Density 20°C	g/ml	0.800
Viscosity at 20°C	mm²/s	1.8
Film thickness	Mikron	0.8
Film consistency		vaseline, thin
Flash point	°C	45
Drying time	Min.	ca. 30
Protection time at:		
- Indoor storage	Months approx.	8 - 12
- outdoor storage	Months approx.	4

**Transport** 

ADR/SDR Class 3, F1, packing group III

UN-Code 1993

Disposal

LVA VeVA / EAK 14 06 03

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch