

STRUB Mirratol 491

Mixer and vehicle protection

Art.-No. 32263

Description

Solvent-free, water-light special oil with very good physical and chemical release properties, ready for use and not sensitive to cold. Particularly suitable for truck mixers, site mixers, loading bridges, superstructures, skips, equipment, tools.

Application

STRUB Mirratol 491 is ready for use, not water soluble, solvent free and economical in consumption. Apply evenly and sparingly to the parts to be protected by sprayer. Wash down adhering concrete with high pressure cleaner or hard water jet. Apply mixer protection after drying, gives the best protection.

Features and advantages

- does not attack metals and plastics
- very good anti-corrosion properties. Does not form resinification or sticky residues.
- STRUB Mirratol 491 can also be used as a stain-free shuttering oil for metal, plastic and wooden shutterings
- VOC solvent-free
- ready for use, universally applicable
- not water soluble
- pleasant odor, smells of lime
- free of heavy metals
- 30 m² 40 m²/liter

Technical data

Color		light
Density at 20°C		0.84
Flash point	°C	160
Pour point	°C	< - 20
Viscosity at 20°C	mm²/s	18
Viscosity at 40°C	mm²/s	9.4

Storage

Do not store below -10°C

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 01 07

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch

ISO 9001|14001, Version 1: 10.03.2015 / WS 1 von 1