

# STRUB Engine Oil Classic HD 30, HD 20W/50

Classic engine oil for classic cars



## **Description**

Modern multigrade engine oils damage your classic car. Therefore, weakly alloyed single-grade engine oils are used. The selected base oils and an additive, which are specially designed for classic car engines, ensure optimum engine lubrication.

### **Application**

For older gasoline and diesel engines at moderate speed where API SE, SD, SC/CD, CC engine oils are required (year/ approx.1955-1975). Please follow manufacturer's instructions.

# Features and advantages

- STRUB Engine Oil Classic are low-alloy engine oils with good corrosion and wear protection. Seals, bearings and rubber parts are not attacked, no shrinkage or swelling of the material possible.
- Temperature range: approx. 5°C to + 35 °C / 20W/50 to + 45°C

# **Specifications**

API SE, SD, SC/CD, CC

#### **Technical data**

SAE		30	20W/50
Aut No		22270	240/2
Art. No.		32379	31863
Density at 20°C		0.890	0.894
Viscosity 100°C	mm²/s	12	17.8
Flash point	°C	224	234
Pour point	°C	- 21	- 21

#### **Transport**

ADR/SDR: No dangerous goods

**Disposal** 

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Swiss Tribology Mühlemattstrasse 5

phone +41 62 785 22 22 fax +41 62 785 22 33 strub@strub-lube.ch