# STRUB Partsynt HC Ultra UHPD 10W/40

High performance diesel engine oil for trucks

Art. No. 30484





#### Description

STRUB Partsynt HC Ultra UHPD is a high performance diesel engine oil. The product is based on highly refined base oils, as well as a selected combination of additives to ensure engine protection and performance.

#### Application

STRUB Partsynt HC Ultra UHPD is suitable for use in heavy duty diesel engines that meet the EURO 2 to EURO 5 emission standards under very harsh conditions. For most trucks with EGR (Exhaust Gas Recirculation), SCR NOx (Selective Cat. Reduction) at extended oil change intervals, as recommended by the vehicle supplier.

#### Features and advantages

- offers maximum oil change intervals even under the most difficult operating conditions
- reduced maintenance due to lowest wear in the engine •
- improved piston cleanliness, due to reduction of deposits, prevents mirror surface formation •
- very good corrosion protection against all metals •
- stay-in-grade •

#### **Specifications**

ACEA E4 /E7, API CI-4 MB-Approval 228.5, MAN M 3277, Scania LDF2, Volvo VDS-3, MTU DDC Type 3, Renault Trucks RXD/RLD-2, Mack EO-M PLUS, EO-N PP, CUMMINS CES 20077, 78, Deutz DQC III-10, Global DHD-1

#### **Technical data**

SAE		10W/40
Art. No.		30484
Density at 20°C	g/cm <sup>3</sup>	0.866
CCS/ Viscosity at - 25°C	mPa.s	6300
Viscosity at 100°C	mm <sup>2</sup> /s	14.6
Viscosity index		150
Pour point	°C	- 32
Flash point	°C	224
TBN	mg KOH/g	12.5
Sulfated ash	%	1.6

## Transport

ADR/SDR

No dangerous goods

### Disposal

LVA VeVA / EAK:

13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

STRUB + Co. AG Swiss Tribology

Mühlemattstrasse 5 CH-6260 Reiden

phone +41 62 785 22 22 +41 62 785 22 33 strub@strub-lube.ch www.strub-lube.ch

ISO 9001|14001, Version 2: 30.10.2014 / MF