

STRUB Partsynt LA-C3 5W/40

High performance fuel-efficient engine oil Low SAPS Technology

Art. No. 31290



Description

STRUB Partsynt LA-C3 is a low SAPS premium low-viscosity engine lubricant for a very wide range of applications.

Application

STRUB Partsynt LA-C3 can be used in many passenger car gasoline and diesel engines with or without turbocharging, for which the international specifications ACEA A3/B4, C3, API SN/CF are required by the manufacturer. The product meets the performance specifications of car manufacturers, such as Mercedes-Benz, BMW, for pump nozzle injection system of VW/ Audi (without Longlife service). Especially for use in diesel engines with exhaust aftertreatment systems /DPF.

Features and advantages

- especially suitable for vehicles with soot particle filter (DPF)
- reduced pollutant emissions
- extreme load capacity at high temperature
- less oil consumption due to low evaporation losses.
- reduction of friction losses
- prevention of sludge formation
- economic efficiency due to extended oil change times
- miscible with all other brand oils

Specifications

ACEA C3, API SN MB 229.31, 229.51, VW 502.00, 505.00, 505.01 BMW Longlife-04, Porsche A40, RN 0700, RN 0710 FORD WSS-M2C917A

Technical data

SAE		5W/40
Art. No.		31290
Color		brown
Density at 20°C	g/cm ³	0.85
Viscosity at 100°C	mm²/s	14.5
Viscosity at 40°C	mm²/s	89
Viscosity index		170
Pour point	°C	- 36
TBN/ Total Base Number	mgKOH/g	7.2
Sulfated ash	%	0.78
Flash point	°C	224

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Swiss Tribology Mühlemattstrasse 5

phone +41 62 785 22 22 fax +41 62 785 22 33 strub@strub-lube.ch www.strub-lube.ch



Transport

ADR/SDR kein Gefahrengut

Entsorgung

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.