

STRUB Partsynt LA-C4 5W/30

High Performance Engine Oil
Low SAPS Technology

Art. No. 32065



Description

STRUB Partsynt LA-C4 is a shear stable stay-in-grade engine oil, which is especially suitable for 3-way catalytic converters and diesel particulate filters in high performance cars and light trucks for diesel and gasoline engines. This specifically supports the longevity of exhaust aftertreatment systems. The HTHS is >3.5 mpa.s.

Application

Specially developed for the latest generation of passenger car gasoline and diesel engines with PDF and 3-way catalytic converters from Renault.

STRUB recommends this product for vehicles that require the following specification:
Renault RN 0720, or ACEA C4.

This oil is not suitable for all engines, observe vehicle operating instructions!

Features and advantages

- reliable cold start due to low viscosity and optimum lubrication
- FEO Fuel Economy, fuel-saving low-viscosity oil
- excellent wear protection, even at full
- provides excellent engine cleanliness - prevents sludge formation or varnishing
- excellent engine protection and economical fuel consumption
- prevents deposits in the engine and turbocharger
- very good corrosion protection against all metals
- stay-in-grade engine oil-
- Long service life of the diesel particulate filter

Specifications

ACEA C4 -12 Renault RN 0720 MB 226.51

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

Technical data

Farbe		brown
Density at 20°C	g/cm ³	0.85
Viscosity at 100°C	mm ² /s	12
Viscosity at 40°C	mm ² /s	69
Viscosity index		172
Pour point	°C	- 36
TBN/ Total Base Number	mgKOH/g	6.3
Sulfated ash	%	< 0.5
Flash point	°C	224

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.