

STRUB 2-T Super TT

Semi-synthetic 2-stroke engine oil

Art.-No. 30316



Description

For air-cooled, small and medium two-stroke engines in motorcycles, forestry and gardening equipment. Suitable for separate lubrication and all types of gasoline. Equally well suited for mixture and pump lubrication (fresh oil automatic). It prevents corrosion, deposits and glow ignitions. The product is low smoke, self-mixing, ash-free and offers very good wear protection.

Application

The mixing ratio is always in accordance with the engine manufacturer's instructions. As a rule, 1 : 50 (2 %).

Features and advantages

- High-performance 2-stroke engine oil with excellent lubricity
- pronounced wear-reducing effect and high scavenging effect
- low ash
- reduces deposits in the combustion chamber and keeps pistons and rings clean
- residues on spark plugs and in the exhaust system are largely prevented
- based on a special mineral oil fraction

Specifications

TISI 1040-2534
ISO L- EGD
JASO FC, FD

Technical data

Color		green
Density at 20°C	g/cm ³	0.864
Viscosity at 40°C	mm ² /s	67
Viscosity at 100°C	mm ² /s	10.2
Viscosity index		137
Pour point	°C	- 21
Flash point COC	°C	99

Transport

ADR/SDR: No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 05

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.