

STRUB Graphitpaste SPG 40

Lubricating paste with very high graphite content

Art.-No. 30461

Description

STRUB Graphite Paste SPG 40 is a paste with a very high content of graphite, built up on an infusible grease (without dripping point).

Application

STRUB Graphite Paste SPG 40 is used as a lubricating, separating and sealing paste or as an assembly paste for flange connections to keep gaskets and the flange itself in good condition. Fields of application: Construction industry, cement industry, mills, foundries, separating lubrication of ejectors for Aluminum die casting, chemical industry, textile and machinery industry, agriculture, etc.

Technical data

Color		black
Saponification type		inorganic
Rest penetration 25°C	1/10 mm	175 - 205
NLGI class		4
Drop point		infusible
Temp. application Solid lubricant	°C	-20 - 600

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 12

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.