



STRUB Molymagus NL-4 C

Grease with excellent emergency running properties

Art.-No. 30453

Description

STRUB Molymagus NL-4 C is a biodegradable grease for applications where black greases have been used until now. Special synergistically acting white solid lubricants give this grease good pressure absorption properties as well as excellent emergency running properties.

Application

Especially for heavily loaded sliding points, spiders on construction machinery, rock crushers, hoists, dredgers, docks, etc.

Features and advantages

- resistant to flexing, high rolling stability, thus low change in consistency under shear, flexing and impact loads
- high rust protection effect, resistant to water
- very high lubricating effect, pronounced EP properties
- resistant to aging, good oxidation stability even at high temperatures
- good storability, easy to convey

Technical data

. Common data		
Color	visual	white
Density	g/cm ³	0.931
Drop point	°C	None
Penetration	10/mm	245 - 275
NLGI class		2 - 3
Thickener system		Aerosil
Oil viscosity at 40°C	mm²/s	1000
Application range	(cSt)	- 25 to + 140
Biodegradable according to CEC-L-33 T-82	°C	> 90 %

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 12

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch