

# STRUB Scaffold grease bright

Modern high-tech assembly grease

### Art.-No. 30566

## Description

STRUB Scaffold Grease bright is a universal grease with a high proportion of synergistically acting solid lubricants. Protects aluminum and zinc alloys against corrosion of any kind and prevents seizure under high static loads thanks to excellent EP properties. Makes screw connections easier to loosen and keeps threaded spindles, joints, bolts, sliding guides smooth-running. The very good adhesion and water resistance allows economical application and targeted use. STRUB Scaffold Grease bright is weather resistant and clean in application.

#### Application

Dry cleaned surfaces or bodies and apply using a lint-free cloth, brush or paintbrush.

#### **Technical data**

Color	visual	white/greenish
Structure		filamentous
NLGI class		2
Penetration	1/10 mm	265 -295
Drip point	°C	190
Temperature - application range	°C	- 25 to + 120

#### Transport

ADR/SDR
---------

No dangerous goods

12

Disposal

•	
LVA VeVA / EAK:	12 01

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

strub@strub-lube.ch www.strub-lube.ch