STRUB HT B Donhad Paste

High temperature resistant lubricating paste



TRIBOLOG

Art. No. 33043

Description

STRUB HT B Donhad Paste an assembly paste of the most modern type mixed with solid lubricant. STRUB HT B Donhad Paste is based on lubricating oils, esters with special additives, adhesive additive and good corrosion protection and demolding properties.

Application

STRUB HT B Donhad Paste is for separating, lubricating and assembling and is used in the following fields: Industry and construction, engine industry, iron and steel industry, rotating fittings, cement industry for the rings on the drum furnaces and for all maintenance in all industrial plants.

Features and advantages

- very good adhesive properties and spreadability •
- excellent resistance to water, bases, ... •
- compatible with all sealing materials •
- can be used in wet and dusty environment •
- very good release agent in the steel and aluminum industry

Technical data

	Norm	Unit	Value
Color	visual	-	white
Rest penetration	25°C	-	265-395
NLGI class		-	2
Stiffener		-	Sodium soap
Operating temperature	-	°C	-20 - 2900
Coefficient of friction	-	-	< 0.13
Density	-	g/cm3	1.8

Transport

ADR/SDR:	No dangerous good	

Disposal	
LVA VeVA / EAK:	12 01 12

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

STRUB + Co. AG Swiss Tribology

strub@strub-lube.ch www.strub-lube.ch