

# **STRUB Inhibitor AL**

For all water-miscible cooling lubricants

Art.-No. 31523

## **Description**

STRUB Inhibitor AL can be used in all water-miscible cooling lubricants, as a highly active corrosion inhibitor to prevent the characteristic tarnish / staining on all aluminum and other metal alloys.

# **Application**

STRUB Inhibitor AL is particularly suitable for the post-inhibition of aqueous cooling lubricant systems. It is important to thoroughly mix the bath volume immediately after adding the inhibitor.

## Dosage

STRUB Inhibitor AL, based on an 8% emulsion ~ 0.16%.

Add 2% to inhibit the cooling lubricant concentrate.

In case of stronger tarnish / stain formation, the application concentration should be increased.

## **Technical data**

Appearance	visual	Brownish
Density at 20°C	g/ml	0.97

**Transport** 

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 99

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch

ISO 9001|14001, Version 1: 26.10.2016 / DF