

STRUB Sharosol 409 V

Formwork oil and concrete release agent, 60.38 % VOC

Art.-No. 30050

Description

STRUB Sharosol 409 V is equally well suited for use on the construction site as in the manufacture of concrete elements. Very modern universal formwork oil. STRUB Sharosol 409 V acts physically and chemically. Its release effect is excellent and the result is clean, smooth, void and stain free concrete surfaces. STRUB Sharosol 409 V has an anticorrosive effect on metal formwork and a preservative effect on wooden formwork. The product works reliably and economically.

Application

For wood, metal and plastic formwork. Apply sparingly and evenly to dry and clean formwork. Unplanned and unused wooden formwork must be soaked with the formwork oil before first use. Any excess formwork oil must be removed with a rubber scraper, especially in the case of non-absorbent formwork.

Features and advantages

- ready for use
- not water soluble
- safe, stain-free, high yield
- low consumption: approx. 70 - 90 m²/kg
- not sensitive to cold
- protects the formwork material

Technical data

Color		Light yellow
Density at 15°C	g/m ³	0.830
Viscosity at 40°C	mm ² /s	ca. 3
Pour point	°C	-18
Flash point	°C	70

Storage

Do not store below -10°C

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.