



STRUB Sharosol BIO 500

Biodegradable allround formwork oil and mixer protection Especially for absorbent formwork

Art.-No. 30001

Description

STRUB Sharosol BIO 500 is particularly suitable for absorbent but also for non-absorbent formwork. Wood, steel as well as coated or plastic-coated formwork. Apply sparingly and evenly on dry and clean formwork. Unplaned (sawed sapwood) unused wooden formwork should be soaked in concrete release agent before first use. Non-absorbent formwork should be stripped briefly with rubber scraper after application with sprayer. Also excellent as a release and cleaning agent for blacktop work.

Features and advantages

- biodegradable, VOC-free
- no stains or pores on concrete surfaces
- double separating effect, chemical and physical and therefore easy demoulding
- very good corrosion protection
- plaster layers, plates, wallpapers can be applied on the concrete after drying without problems
- concrete after drying
- low consumption: 1 liter for approx. 65 85 m² depending on formwork type
- suitable also for heated formwork > 80°C (ask our technical department, because the viscosity has to be adjusted resp. considered according to the temperature)
- biodegradable according to OECD 301 B guidelines: > 85 %

Technical data

Density at 20°C	g/cm ³	0.818
Viscosity at 20°C	mm²/s	5.2
Viscosity at 40°C	mm²/s	3.5
Flash Point	°C	125
Pour Point	°C	- 6

Storage

Do not store below 0°C

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 07

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch

ISO 9001|14001, Version 2: 22.01.2016 / WS 1 von 1