

# STRUB Diamant 60-CL

Thread cutting spray, VOC 136.20g

**Art.-No. 31402**

## Description

All-round lubricant for joints, bolts, chains, hinges, etc.

Also acts as an additive in lubricating oils to prevent galling, seizing of metal couples. Excellent as thread cutting oil in chrome steel.

## Application

Cutting, sawing, tapping, thread forming, punching, bending, spinning, forming in steel and highest alloyed metals, including chrome steel. As corrosion protection (ASTM D 665 pass) for indoor storage and sea transport (additional film recommended). Metalworking, industrial maintenance, wood, paper, plastics, automotive, aircraft industries, shipyards.

Almost unlimited lubricant use.

## Features and advantages

- High pressure (EP)
- anti-wear (AW)
- water displacing (DW)
- excellent creep capillary action
- ageing and heat stable (~ 250°C active ingredient)
- long term lubrication

## Technical data

Color	greenish
Shape	liquid
Density 20°C	> 1.200 gr/ml
Solubility in water	insoluble
Explosion limits: lower upper	0,6 % by volume 6,5 vol. %
Ignition temperature	250°C (propellant gas highly flammable F+)
Vapor pressure 20°C	< 1 mbar
Temperature application	-30°C - 250°C

## Transport

ADR/SDR UN 1950, Class 2, 5F

## Disposal

LVA VeVA / EAK 12 01 06

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.