

STRUB HTP-Spray 400 ml

High temperature paste, release, lubricating and assembly spray, VOC 182.52g

Art.-No. 30824

Description

Good adhesion spray. Based on polar oils, solid lubricants and special adhesive additives. Very good anti-corrosion properties.

Application

Solid lubricant spray of the most modern type. Use as a separating, lubricating and assembly spray in the field of tramways, industry and plant construction, automotive industry, iron and steel industry, for ladle gate valves, cement industry for rings on rotary kilns, as well as for all maintenance in all industrial plants.

Features and advantages

- very good resistance to water, weak alkalis and acids
- compatible with all sealing materials
- can also be used in wet and dusty conditions

Technical data

Color	visual	copper colored
Structure		good adhesion
NLGI class		2
Drop point	°C	none
Use as release and lubricating paste in the presence of oxygen	°C	approx. 250
Use as release paste without presence of oxygen	°C	-20°C - 1'200°C
Oxidation stability at 100°C	psi	4
Oxidation stability at 250°C	psi	10

Transport

ADR/SDR UN 1950, 2, 5 F

Disposal

LVA VeVA / EAK 15 01 04, 16 05 05

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.