

STRUB Universalspray Z

Emergency running lubricant spray, VOC 254.20g

Art.-No. 30698

Description

STRUB Universalspray Z is a matt black MoS₂-based high and low temperature bonded coating spray with additional synergistically acting solid lubricants.

Application

STRUB Universalspray is used for slideways and suspension tracks, threaded spindles, gears, gearing, joints, sliding seats, leaf springs, bolts, hinges, chains, sliding surfaces, etc.

Spray STRUB Universal Spray Z onto degreased surfaces from a distance of approx. 10 - 30 cm. Do not use in the presence of open fire or sources of ignition.

Features and advantages

The applied bonded coating dries quickly and cures in air after only a few minutes. The adhesion and mechanical resistance of the dry sliding film can be further improved by heating to 70 - 150°C for 1 1/2 hours. Thanks to its high capillary action, STRUB Universalspray Z reaches even the finest crevices and prevents friction and wear even at the highest surface pressures of metal surfaces (protective film with 10'000 layers of laminar solid lubricant particles). The emergency running properties with the lowest friction coefficient are guaranteed.

Technical data

Temperature application range after curing under exclusion of air	°C	-180 - +450 -180 - +650
--	----	----------------------------

Transport

ADR/SDR UN 1950

Disposal

LVA VeVA / EAK 14 06 03

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.