

1 von 1

STRUB Zink Spray

Micro fine zinc powder coating in spray, VOC 276.00g

Art.-No. 30695

Description

Microfine zinc powder in spray for temperatures from - 40°C to + 490°C. Color: matt gray.

Application

Spray STRUB Zinc Spray onto degreased surfaces from a distance of approx. 10 - 30 cm. Do not use in the presence of open fire or ignition sources. The applied film dries quickly and protects permanently against corrosion.

Features and advantages

- contains 99% microfine zinc powder
- salt water resistant
- protects permanently against corrosion
- forms firmly adhering, fast drying permanent primer
- suitable as electrochemical corrosion protection

Technical data

Operating temperature	°C	-40°C to +490°C
-----------------------	----	-----------------

Transport

ADR/SDR Class 2 VG **UN-Code** 1950

Disposal

LVA VeVA / EAK 15 01 04

15 01 10

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch +41 62 785 22 33 Swiss Tribology CH-6260 Reiden fax www.strub-lube.ch

ISO 9001|14001, Version 1: 30.07.2013 / MF