

STRUB Food Adhesive Lube PTFE H1 Spray 500 ml

high quality lubricant for food, textile, plastic, machinery industry with solid lubricant NSF food release, VOC 215.67g.

Art.-No. 33204

Description

Fully synthetic, silicone-free lubricant, release agent and corrosion inhibitor with solid lubricant of the highest purity class.

Whitish liquid. Virtually odorless and tasteless, non-toxic.

Good viscosity-temperature behavior (high viscosity index), good wear protection, excellent lubricity, sealing compatibility, high oxidation stability and good corrosion protection for ferrous, light and non-ferrous metals (Fe, Al, Cu). Low evaporation and only very low coking tendency.

Application

Plain bearings, locks, conveyor belts, bolts, joints, hinges, roller shutters, ropes

Certificates

NSF 156059, Halal, Kosher

Features and advantages

- synthetic, whitish
- good penetration
- water repellent .
- rust protection •
- wear protection •
- oxidation stable •
- tasteless •
- temperature application range -10 to +150°C

Technical data

Color	visual	whitish
Viscosity	20°C	1,8-2,2 mm ² /s
Density	20°C	0,84 g/cm ³
Flash point	°C	43°C

Transport ADR/SDR

HAZARDOUS

UN 1950 PRESSURIZED GAS PACKAGES, 2.1, ENVIRONMENTALLY

Disposal LVA VeVA / EAK

Contents 16 05 04, empty packaging 15 01 04

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

fax

STRUB + Co. AG Swiss Tribology

phone +41 62 785 22 22 +41 62 785 22 33 strub@strub-lube.ch www.strub-lube.ch