

STRUB Vulcolube Hot Steam Cylinder Oil 1500

ISO VG 1500

Art. No. 33061

Description

STRUB Vulcolube Hot Steam Cylinder Oil 1500 is suitable for the lubrication of steam engines which are operated at high temperatures and which require high-viscosity lubricating oils of particularly good thermal stability.

STRUB Vulcolube Hot Steam Cylinder Oil 1500 has very low evaporation losses even under high thermal load. This ensures lubrication of the cylinders and the parts exposed to steam. The formation of coke- and asphalt-like residues, which can be the cause of seizure of piston rings, slides and valves, is prevented.

STRUB Vulcolube Hot Steam Cylinder Oils 1500 are special lubricating oils. They are manufactured from carefully selected mineral base oils and synthetic components using state-of-the-art production methods. STRUB Vulcolube hot steam cylinder oils 1500 form well adhering, highly resilient lubricating films even when used sparingly.

Application

STRUB Vulcolube Hot Steam Cylinder Oil 1500 is recommended for use in intermittently operating steam machines as a loss lubricant at steam inlet temperatures up to 380° C.

STRUB Vulcolube Hot Steam Cylinder Oil 1500 is also suitable when a high viscosity lubricating oil is required by the manufacturer, e.g. for mechanical gears, bearings and slideways.

Features and advantages

- Very high thermal stability
- High aging resistance
- Very low evaporation loss
- Good lubricating properties
- Excellent film strength (economical consumption)

Viscosity class		ISO VG 1500
Viscosity at 40°C	mm/ ² s	1520
Viscosity index		85
Flash point	°C	308
Coke residue according to Conradson	Mass %	<5.0
Corrosion effect on copper	Corr. degree	1-100 A3

Transportation

ADR/SDR: Not a dangerous good

Disposal

LVA VeVA / EAK: 15 01 10

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.

STRUB + Co. AG Mühlemattstrasse 5 phone +41 62 785 22 22 strub@strub-lube.ch
Swiss Tribology CH-6260 Reiden fax +41 62 785 22 33 www.strub-lube.ch